

Sec. 22a-133k-3. Ground-water remediation standards

(a) General.

(1) Remediation of a ground-water plume shall result in the attainment of: (A) the requirements concerning surface water protection set forth in subsection (b) of this section and the requirements concerning volatilization set forth in subsection (c) of this section; or (B) the background concentration for ground water for each substance in such plume.

(2) Remediation of a ground-water plume in a GA area shall also result in the reduction of each substance therein to a concentration equal to or less than the background concentration for ground water of such substance, except as provided in subsection (d) of this section.

(3) Remediation of a ground-water plume in a GB area shall also result in the reduction of each substance therein to a concentration such that such ground-water plume does not interfere with any existing use of the ground water.

(b) Surface-water protection criteria.

(1) Except as provided in subdivision (2) of this subsection, remediation of a ground-water plume which discharges to a surface water body shall result in the reduction of each substance therein to a concentration which is consistent with subdivision (2)(C) of subsection (g) of this section and which is equal to or less than the surface-water protection criterion or an alternative surface-water protection criterion established in accordance with subdivision (3) of this subsection.

(2) If a ground-water plume (A) discharges to a wetland or an intermittent stream, or (B) the areal extent of such ground-water plume occupies more than 0.5%, or other percentage which is approved in writing by the Commissioner, of the upstream drainage basin of the stream to which such plume discharges measured from the intersection of stream and such ground-water plume, each substance therein shall be remediated to a concentration equal to or less than the applicable aquatic life criteria contained in Appendix D to the most recent Water Quality Standards, or equal to or less than an alternative water quality criterion adopted by the Commissioner in accordance with section 22a-426 of the General Statutes and paragraph 12b of the Water Quality Standards effective May 15, 1992.

(3) Alternative surface-water protection criteria.

Alternative surface-water criteria may be calculated in accordance with subparagraph (A) of this subdivision or may be approved in writing by the Commissioner in accordance with subparagraph (B) of this subdivision.

(A) An alternative surface-water protection criterion may be calculated for a substance in Appendix D of the most recent Water Quality Standards by multiplying the lower of the human health or aquatic life criterion for such substance in said Appendix D by where Q_{plume} is equal to the average daily discharge of polluted ground water from the subject ground-water plume.

(B) The Commissioner may approve an alternative surface-water protection criterion to be applied to a particular substance at a particular release area. Any person requesting such approval shall submit to the Commissioner: (i) a report on the flow rate, under seven day ten year low flow conditions, of the surface water body into which the subject ground water plume discharges (ii) a report on other surface water or ground water discharges to the surface water body within one-half mile upstream of the areal extent of the ground-water

plume, (iii) a report on the instream water quality, (iv) a report on the flow rate of the ground-water discharge from such release area to the surface water body and the extent and degree of mixing of such discharge in such surface water, and (v) and any other information the Commissioner reasonably deems necessary to evaluate such request. The Commissioner shall not approve an alternative surface-water protection criterion under this subparagraph unless the requester demonstrates that such criterion will protect all existing and proposed uses of such surface water.

(c) Volatilization criteria.

(1) Except as specified in subdivisions (2), (3), (4) and (5) of this subsection, all ground water polluted with a volatile organic substance within 15 feet of the ground surface or a building, shall be remediated such that the concentration of each such substance is equal to or less than the applicable residential volatilization criterion for ground water.

(2) If ground water polluted with a volatile organic substance is below a building used solely for industrial or commercial activity, such ground water shall be remediated such that the concentration of such substance is equal to or less than the applicable industrial/commercial volatilization criterion for ground water, provided that an environmental land use restriction is in effect with respect to the parcel or portion thereof upon which such building is located, which restriction ensures that the parcel or portion thereof will not be used for any residential purpose in the future and that any future use of the parcel or portion thereof is limited to industrial or commercial activity;

(3)

(A) Remediation of a volatile organic substance to the volatilization criterion for ground water shall not be required if the concentration of such substance in soil vapors below a building is equal to or less than (i) the residential volatilization criterion for soil vapor or (ii) the industrial/commercial volatilization criterion for soil vapor, if such building is solely used for industrial or commercial activity and, an environmental land use restriction is in effect with respect to the parcel or portion thereof upon which such building is located, which restriction ensures that the parcel or portion thereof will not be used for any residential purpose in the future and that any future use of the parcel or portion thereof is limited to industrial or commercial activity.

(B) The requirements of subdivision (1), (2), and (3) of this subsection do not apply if: (i) measures acceptable to the Commissioner have been taken to prevent the migration of such substance into any overlying building, (ii) a program is implemented to maintain and monitor all such measures, and (iii) notice of such measures has been submitted to the Commissioner on a form furnished by him which notice includes (aa) a brief description of the areal extent of the ground-water plume and of the area which exceeds any such volatilization or soil vapor criterion; (bb) a brief description of the method of controlling the migration of such substance into any overlying building; (cc) a plan for the monitoring and maintenance of such control method; and (dd) a map showing all existing buildings, the areal extent of the ground-water plume, and the location of such control method.

(4) Site-specific and alternative volatilization criteria.

(A) Site-specific residential volatilization criteria for ground water or soil vapor may be calculated using the equations in Appendix G to sections 22a-133k-1 through 22a-133k-3 of the Regulations of Connecticut State Agencies.

(B) The Commissioner may approve an alternative volatilization criterion for ground water or for soil vapor to be applied to a substance at a particular release area. The Commissioner shall not approve any alternative criterion under this subparagraph unless it has been demonstrated that such criterion will ensure that volatile organic substances from such ground water or soil do not accumulate in the air of any structure used for residential activities at a concentration which, (i) for any carcinogenic substance creates a risk to human health in excess of a 10^{-6} excess lifetime cancer risk level, and for any non-carcinogenic substance does not exceed a hazard index of 1, or (ii) for a ground-water plume polluted with multiple volatile organic substances does not exceed a cumulative excess cancer risk level of 10^{-5} for carcinogenic substances, and for non-carcinogenic substances with the same target organ, the cumulative hazard index does not exceed 1.

(5) Exemption from volatilization criteria.

(A) The volatilization criteria do not apply to ground water polluted with volatile organic substances, where the water table is less than fifteen feet below the ground surface, if no building exists over the ground water polluted with volatile organic substances at a concentration above the applicable volatilization criteria, and (i) it has been documented that best efforts have been made to ensure that each owner of any parcel of land or portion thereof overlying such polluted ground water records an environmental land use restriction which ensures that no building is constructed over such polluted ground water; or (ii) the Commissioner has approved in writing a request demonstrating that no building can reasonably be expected to be constructed over the subject ground water or that natural attenuation or other methods of remediation will, within five years, reduce the concentration of volatile organic substances in such ground water to a concentration equal to or less than the applicable volatilization criteria.

(B) The volatilization criteria for ground water underlying an existing building do not apply to ground water polluted with volatile organic substances where the Commissioner has approved in writing and there have been implemented an indoor air monitoring program and measures to control the level of any such volatile organic substances in the air of the subject building.

(i) Any person seeking the Commissioner's approval of an indoor air monitoring program shall submit to him: a detailed written plan describing the proposed indoor air monitoring program, including but not limited to a description of the distribution and concentration of volatile organic compounds beneath the building, the location of proposed monitoring points, the proposed frequency of monitoring, the parameters to be monitored, and a description of proposed actions to be taken in the event such monitoring indicates that the monitored parameters exceed proposed specified concentrations and a proposed schedule for reporting to the Commissioner on the results of such monitoring for as long as monitoring is conducted at the site.

(ii) In approving any indoor air monitoring program pursuant to this subdivision, the Commissioner may impose any additional conditions he deems necessary to ensure that the program adequately protects human health. In the event that the Commissioner approves an indoor air monitoring program pursuant to this subparagraph, any person implementing such program shall perform all actions specified in the approved plan, and any additional measures specified by the Commissioner in his approval of such plan.

(d) Applicability of Ground-water Protection Criteria.

(1) Ground water in a GA area may be remediated to a concentration for each substance therein equal to or less than the ground-water protection criterion for each such substance if, with respect to the subject ground-water plume: (A) the background concentration for ground water is equal to or less than such ground-water protection criterion; (B) a public water supply distribution system is available within 200 feet of the subject parcel, parcels adjacent thereto, and any parcel within the areal extent of such plume; (C) such ground-water plume is not located in an aquifer protection area; and (D) such ground-water plume is not located within the area of influence of any public water supply well.

(2) If prior to any ground-water remediation the maximum concentration of a substance in a ground-water plume in a GA area is equal to or less than the ground-water protection criteria, remediation of ground water to achieve background ground-water concentration is not required, provided that the extent of the ground-water plume is not increasing over time and, except for seasonal variations, the concentration of the subject substance in such ground-water plume is not increasing at any point over time.

(3) Any ground water in a GB area and which is used for drinking or other domestic purposes shall be remediated to reduce the concentration of each substance therein to a concentration equal to or less than the applicable ground-water protection criterion until such time as the use of such ground water for drinking or other domestic purposes is permanently discontinued.

(e) Technical Impracticability of Ground-water Remediation.

(1) Exemption from Background Due to Technical Impracticability

If remediation of a ground-water plume in a GA area to achieve compliance with subdivision (2) of subsection (a) of this section has reduced the concentration of a polluting substance to less than the ground-water protection criterion, and if further reduction of such concentration is technically impracticable, no further remediation of such ground-water plume for such substance shall be required.

(2) Variance Due to Technical Impracticability of Ground-water Remediation

The Commissioner may grant a variance from any of the requirements of this section if he finds that: non-aqueous phase liquids that cannot be contained or removed in accordance with R.C.S.A. section 22a-133k-2(g) are present; remediation to the extent technically practicable has reduced the concentration of pollutants in ground water to steady-state concentrations that exceed any applicable criteria; or achieving compliance with the applicable criteria is technically impracticable as determined using Directive No. 9234.2-25 issued September 1993 by the U.S. Environmental Protection Agency's Office of Solid Waste and Emergency Response.

(A) Any person requesting a variance pursuant to this subsection from any ground-water protection criterion shall submit: (i) information concerning the concentration of each substance in the ground-water plume with respect to which a variance is sought; (ii) information demonstrating that (aa) the extent of the ground-water plume which exceeds such ground-water protection criterion has been reduced to the extent technically practicable, or (bb) it is not technically practicable to reduce the extent of the ground-water plume; (iii) the results of a study conducted to determine the risks to human health posed by the polluted ground water remaining after such reduction; (iv) if such study shows a risk

or a potential risk to human health, a plan to eliminate such risk or potential risk; (v) an application to change the ground-water classification of such polluted ground water to GB in accordance with section 22a-426 of the General Statutes; and (vi) any other information the Commissioner reasonably deems necessary to evaluate such request.

(B) Any person requesting a variance pursuant to this subsection from the requirement to remediate ground water to a concentration which does not exceed the applicable surface-water protection criteria shall submit information concerning the concentration of each substance in the ground-water plume with respect to which a variance is sought. If such information demonstrates that any such concentration exceeds any applicable surface-water protection criterion, such person shall also submit: (i) a map showing the areal extent of the ground-water plume that exceeds such surface-water protection criterion, and (ii) a plan for controlling the migration of such substance to the receiving surface water body.

(C) If the Commissioner grants a variance pursuant to this subsection from any ground-water protection criterion, the person receiving the variance shall, no later than thirty days after the date of granting of such variance, submit to the Commissioner on a form prescribed and provided by him: (i) certification that written notice of the extent and degree of such pollution has been provided to each owner of property overlying the subject ground-water plume at which it is not technically practicable to remediate a substance to a concentration equal to or less than the ground-water protection criterion; (ii) certification that written notice of the presence of pollution on each such parcel and a description of the extent and degree of such pollution has been sent to the Director of Health of the municipality or municipalities in which the ground-water plume is located; and (iii) certification that best efforts have been made to ensure that each owner of property overlying the subject ground-water plume records an environmental land use restriction which ensures that the subject ground-water plume is not used for drinking or other domestic purposes;

(D) If the Commissioner grants a variance pursuant to this subsection from the requirement to remediate ground water to a concentration which does not exceed the applicable surface-water protection criteria, the person receiving the variance shall perform all actions specified in the plan submitted with the request for such variance, and any additional actions required by the Commissioner in his approval of such plan or granting of such variance.

(f) Incidental Sources.

Remediation criteria for ground water do not apply to:

(1) Trihalomethanes resulting from releases of drinking water from a public water supply system; or

(2) Metals, petroleum hydrocarbons or semi-volatile substances provided such pollution is the result of:

(A) An incidental release due to the normal operation of motor vehicles, not including refueling, repair or maintenance of a motor vehicle; or

(B) Normal paving and maintenance of a consolidated bituminous concrete surface provided such bituminous concrete surface has been maintained for its intended purpose.

(g) Applying the Criteria for Ground Water.

Ground-water monitoring shall be conducted in accordance with this subsection for any ground-water plume and for any release area remediated in accordance with SECTIONS

22a-133k-1 through 22a-133k-3, inclusive, of the Regulations of Connecticut State Agencies, except for those release areas remediated solely to address exceedances of direct exposure criteria in accordance with SECTION 22a-133k-2(b).

(1) Ground-water Monitoring.

Monitoring shall be designed to determine:

(A) The effectiveness of any soil remediation to prevent the pollution of ground water by substances from the release area;

(B) The effectiveness of any measures to render soil environmentally isolated;

(C) The effectiveness of any remediation taken to eliminate or minimize health or safety risks associated with such release or identified in any risk assessment conducted in accordance with subsection (e)(2) of this section or otherwise identified;

(D) Whether a substance in ground water in a GA area or an aquifer protection area meets the background concentration or ground-water protection criteria, as applicable, in accordance with the provisions of subdivision (2) of this subsection;

(E) Whether a substance in ground water meets the surface-water protection criteria and the applicable volatilization criteria in accordance with the provisions of subdivision (2) of this subsection; and

(F) Whether a ground-water plume in a GB area interferes with any existing use of the ground water for a drinking water supply or with any other existing use of the ground water, including but not limited to, industrial, agricultural or commercial purposes.

(2) Compliance with Criteria for Ground Water.

(A) General.

(i) Analytical results of samples used for determining compliance with an applicable remedial criterion for a substance shall be collected after:

(I) All remedial actions conducted to achieve compliance with pollutant mobility and ground-water criteria for such substance have been concluded, other than natural attenuation of a ground-water plume or the recording of an environmental land use restriction;

(II) The aquifer is no longer subject to the transient effects on hydraulic head attributable to withdrawal from, or injection to, ground water for the purpose of remediation, or other effects due to site redevelopment or remediation;

(III) Any changes to the geochemistry, induced by remedial actions or monitoring well construction methods which might influence the concentration of such substance, have stabilized and equilibrium geochemical conditions are established; and

(IV) The concentration of such substance at each sampling location that represents the extent and degree of the ground-water plume is not increasing over time, except as a result of either natural attenuation or seasonal variations.

(ii) For determining compliance with an applicable remedial criterion for a substance, a minimum of four sampling events shall be performed which reflect seasonal variability on a quarterly basis, provided that all sampling events used to demonstrate compliance were performed within two years prior to the most current sampling event used to determine compliance, with the exception of monitoring conducted in accordance with subparagraph (D)(ii) of this subsection.

(iii) The Commissioner may approve in writing an alternative method of determining compliance with an applicable remedial criterion for a substance utilizing emerging

technologies for which guidance, standard or industrial code has been published by a regulatory agency, governmental advisory group, or other recognized professional organization, at the time of the approval.

(B) Compliance with Ground-water Protection Criteria or Background.

Compliance with the ground-water protection criterion for a substance in ground water or background concentration for ground water for such substance is achieved when the sampling locations are representative of the subject ground-water plume and (i) the analytical results for such substance at all such sampling locations are equal to or less than either the ground-water protection criterion for such substance or the background concentration for ground water, whichever is applicable, as determined by subsection (d) of this section or (ii) a representative sampling program consisting of not less than twelve consecutive monthly samples from each such sampling location has been used to characterize the ground-water plume and the ninety-five percent upper confidence level of the arithmetic mean of all results of laboratory analyses of such samples for such substance are equal to or less than the criterion for such substance.

(C) Compliance with Surface-water Protection Criteria.

Compliance with a surface-water protection criterion for a substance in ground water is achieved when the sampling locations are representative of the subject ground-water plume and (i) the ninety-five percent upper confidence level of the arithmetic mean of all sample results representative of the subject ground water plume is equal to or less than such criterion; or (ii) the concentration of such substance in that portion of such plume which is immediately upgradient of the point at which such ground-water discharges to the receiving surface-water body is equal to or less than the applicable surface-water protection criterion.

(D) Compliance with Volatilization Criteria.

A volatile substance may be remediated to a concentration as specified in either subdivision (2)(D)(i) or subdivision (2)(D)(ii) of this subsection.

(i) Compliance with volatilization criteria in ground water.

Compliance with a volatilization criterion for a substance in ground water is achieved when the sampling locations are representative of the subject ground-water plume and the results of all laboratory analyses of samples for such substance are equal to or less than the applicable volatilization criterion as determined by subsection (c) of this section.

(ii) Compliance with volatilization criteria in soil vapor.

Compliance with a volatilization criterion for a substance in soil vapor is achieved when the sampling locations and frequency are representative of the subject soil vapor, including seasonal variability, and the results of all laboratory analyses of samples for such substance are equal to or less than the applicable volatilization criterion.

(3) Matrix interference effects.

If any applicable criterion for a substance in ground water is less than the concentration for such substance that can be consistently and accurately quantified in a specific sample due to matrix interference effects, the following action shall be taken:

(A)

(i) "Test Methods for Evaluating Solid Waste : Physical/Chemical Methods," SW-846, U.S. Environmental Protection Agency, Office of Solid Waste, Washington D.C. 20460 shall be consulted to determine if an analytical method sufficiently sensitive to achieve the

applicable analytical detection limit was used to conduct the analysis of the subject substance. If there is available an alternative analytical method which is sufficient to achieve the required analytical detection limit, appropriate for the sample matrix, and has been approved by EPA or approved in writing by the Commissioner, the subject ground water shall be re-analyzed for the subject substance using such alternative method.

(ii) If a sample has been analyzed by one or more analytical methods in accordance with subparagraph (A)(i) of this subdivision and the applicable analytical detection limit has not been achieved due to matrix interference effects, such method(s) shall be modified in order to compensate for such interferences, in accordance with analytical procedures specified by EPA within the scope of the analytical method.

(B) If, after re-analyzing the subject ground water and attempting to compensate for matrix interference effects in accordance with subparagraph (A) of this subdivision, any applicable criterion for a substance in ground water is less than the concentration for such substance that can be consistently and accurately quantified in a specific sample due to matrix interference effects, compliance with such criterion shall be achieved when such ground water has been remediated to the lowest concentration for such substance which can be consistently and accurately quantified without matrix interference effects.

(C) A detailed summary of all measures taken to overcome matrix interference effects and a determination of the lowest alternative quantification level applicable to the analysis of such substance shall be prepared and, if requested by the Commissioner in writing, shall be submitted to the Commissioner for his review and approval.

(h) Additional Polluting Substances

(1) With respect to a substance in ground water for which a ground-water protection criterion is not specified in sections 22a-133k-1 through 22a-133k-3, inclusive, of the Regulations of Connecticut State Agencies, the Commissioner may approve in writing a ground-water protection criterion to apply to such substance. Any person requesting approval of a ground-water protection criterion for such substance shall submit to the commissioner (A) a risk-based ground-water protection criterion for such substance calculated in accordance with subdivision (2) of this subsection, (B) the analytical detection limit for such substance, (C) a description of the organoleptic properties of such substance. Before approving a ground-water protection criterion the Commissioner shall consider the proposed risk-based ground-water protection criterion for such substance, the analytical detection limit for such substance, the organoleptic effects of such substance, any information about the health effects such substance may cause due to exposure pathways not accounted for in the proposed risk-based ground-water protection criterion, and any other information that the Commissioner reasonably deems necessary.

(2) The risk-based ground-water protection criterion shall be calculated using the following equations:

(A) For carcinogenic substances;

$$GWPC = \left[\frac{Risk}{CSF} \right] \times \left[\frac{BW \times AT}{IR \times EF \times ED \times CF} \right]$$

(B) For non-carcinogenic substances:

$$GWPC = [Rfd \times HI] \times \left[\frac{(BW \times AT \times SA)}{(IR \times EF \times ED \times CF)} \right]$$

(C) The abbreviations used in subparagraphs (A) and (B) of this subdivision shall be interpreted in accordance with the following table and shall be assigned the values specified therein:

Term	Description	Units	Value
GWPC _{RB}	Risk-based Ground-water protection Criterion	ug/l	calculated
Risk	Target Cancer Risk Level	unitless	1.0E-06
HI	Hazard Index	unitless	1.0
CSF	Cancer slope Factor	(mg/kg-day) ⁻¹	substance-specific
RFD	Reference Dose	mg/kg-day	substance-specific
IR	Ingestion Rate	l/day	2
EF	Exposure Frequency	days/year	365
ED	Exposure Duration	years	70
CF	Conversion Factor	mg/ug	0.001
BW	Body Weight	kg	70
AT	Averaging Time,	days	25550
SA	Source Allocation	unitless	0.2

(i) Additional Remediation of Ground Water.

Nothing in sections 22a-133k-1 through 22a-133k-3, inclusive, of the Regulations of Connecticut State Agencies shall preclude the Commissioner from taking any action necessary to prevent or abate pollution, or to prevent or abate any threat to human health or the environment. If the presence of any substance impairs the aesthetic quality of any ground water which is or can reasonably be expected to be a source of water for drinking or other domestic use, additional remediation shall be conducted in order to reduce the concentration of such substance to a concentration appropriate for such use.

Appendix A to Sections 22a-133k-1 through 22a-133k-3 of the Regulations of Connecticut State Agencies Direct Exposure Criteria for Soil

Substance	Residential Criteria in mg/kg (ppm)	Industrial/ Commercial Criteria in mg/kg
------------------	--	---

Regulations of Connecticut State Agencies

		(ppm)
Volatile Organic Substances		
Acetone	500	1000
Acrylonitrile	1.1	11
Benzene	21	200
Bromoform	78	720
2-Butanone(MEK)	500	1000
Carbon tetrachloride	4.7	44
Chlorobenzene	500	1000
Chloroform	100	940
Dibromochloromethane	7.3	68
1,2-Dichlorobenzene	500	1000
1,3-Dichlorobenzene	500	1000
1,4-Dichlorobenzene	26	240
1,1-Dichloroethane	500	1000
1,2-Dichloroethane	6.7	63
1,1-Dichloroethylene	1	9.5
cis-1,2-Dichloroethylene	500	1000
trans-1,2-Dichloroethylene	500	1000
1,2-Dichloropropane	9	84
1,3-Dichloropropene	3.4	32
Ethylbenzene	500	1000
Ethylene dibromide (EDB)	0.007	0.067
Methyl-tert-butyl-ether	500	1000
Methyl isobutyl ketone	500	1000
Methylene chloride	82	760
Styrene	500	1000
1,1,1,2-Tetrachloroethane	24	220
1,1,2,2-Tetrachloroethane	3.1	29
Tetrachloroethylene	12	110
Toluene	500	1000
1,1,1-Trichloroethane	500	1000
1,1,2-Trichloroethane	11	100
Trichloroethylene	56	520
Vinyl chloride	0.32	3
Xylenes	500	1000

Regulations of Connecticut State Agencies

Semivolatile Substances

Acenaphthylene	1000	2500
Anthracene	1000	2500
Benzo(a)anthracene	1	7.8
Benzo(b)fluoranthene	1	7.8
Benzo(k)fluoranthene	8.4	78
Benzo(a)pyrene	1	1
Bis(2-chloroethyl)ether	1	5.2
Bis(2-chloroisopropyl) ether	8.8	82
Bis(2-ethyl hexyl) phthalate	44	410
Butyl benzl phthalate	1000	2500
2-chlorophenol	340	2500
Di-n-butyl phthalate	1000	2500
Di-n-octyl phthalate	1000	2500
2,4-Dichlorophenol	200	2500
Fluoranthene	1000	2500
Fluorene	1000	2500
Hexachloroethane	44	410
Hexachlorobenzene	1	3.6
Naphthalene	1000	2500
Pentachlorophenol	5.1	48
Phenanthrene	1000	2500
Phenol	1000	2500
Pyrene	1000	2500

Inorganic Substances

Antimony	27	8200
Arsenic	10	10
Barium	4700	140000
Beryllium	2	2
Cadmium	34	1000
Chromium, trivalent	3900	51000
Chromium, hexavalent	100	100
Copper	2500	76000
Cyanide	1400	41000

Regulations of Connecticut State Agencies

Lead	400	1000
Mercury	20	610
Nickel	1400	7500
Selenium	340	10000
Silver	340	10000
Thallium	5.4	160
Vanadium	470	14000
Zinc	20000	610000
Pesticides, PCB's and Total Petroleum Hydrocarbons (TPH)		
Alachlor	7.7	72
Aldicarb	14	410
Atrazine	2.8	26
Chlordane	0.49	2.2
Dieldrin	0.038	0.36
Endrin	20	610
2-4 D	680	20000
Heptachlor epoxide	0.067	0.63
Heptachlor	0.14	1.3
Lindane	20	610
Methoxychlor	340	10000
Toxaphene	0.56	5.2
PCB's	1	10
TPH -Total Petroleum Hydrocarbons by EPA Method 418.1 (This method shall not be used for the analysis of samples collected after June 30, 2009)	500	2500
Extractable Total Petroleum Hydrocarbons by ETPH Analysis (This method may be used for the analysis of samples collected on or after June 22, 1999)	500	2500

Appendix B to Sections 22a-133k-1 through 22a-133k-3 of the Regulations of Connecticut State Agencies Direct Exposure Criteria for Soil

Regulations of Connecticut State Agencies

Substance	GA, GAA Mobility Criteria in mg/kg (ppm)	GB Mobility Criteria in mg/kg (ppm)
Volatile Organic Sub- stances		
Acetone	14	140
Acrylonitrile	0.01	0.1
Benzene	0.02	0.2
Bromoform	0.08	0.8
2-Butanone(MEK)	8	80
Carbon tetrachloride	0.1	1
Chlorobenzene	2	20
Chloroform	0.12	1.2
Dibromochloromethane	0.01	0.1
1,2-Dichlorobenzene	3.1	3.1
1,3-Dichlorobenzene	12	120
1,4-Dichlorobenzene	1.5	15
1,1-Dichloroethane	1.4	14
1,2-Dichloroethane	0.02	0.2
1,1-Dichloroethylene	0.14	1.4
cis-1,2-Dichloroethylene	1.4	14
trans-1,2-Dichloroethylene	2	20
1,2-Dichloropropane	0.1	1.0
1,3-Dichloropropene	0.01	0.1
Ethyl benzene	10.1	10.1
Ethylene dibromide (EDB)	0.01	0.1
Methyl-tert-butyl-ether	2	20
Methyl isobutyl ketone	7	14
Methylene chloride	0.1	1.0
Styrene	2	20
1,1,1,2-Tetrachloroethane	0.02	0.2
1,1,2,2-Tetrachloroethane	0.01	0.1
Tetrachloroethylene	0.1	1

Regulations of Connecticut State Agencies

Substance	GA, GAA Mobility Criteria in mg/kg (ppm)	GB Mobility Criteria in mg/kg (ppm)
Toluene	20	67
1,1,1-Trichloroethane	4	40
1,1,2-Trichloroethane	0.1	1
Trichloroethylene	0.1	1.0
Vinyl chloride	0.04	0.40
Xylenes	19.5	19.5
Semivolatile Substances		
Acenaphthylene	8.4	84
Anthracene	40	400
Benzo(a)anthracene	1	1
Benzo(b)fluoranthene	1	1
Benzo(k)fluoranthene	1	1
Benzo(a)pyrene	1	1
Bis(2-chloroethyl)ether	1	2.4
Bis(2-chloroisopropyl)ether	1	2.4
Bis(2-ethyl hexyl)phthalate	1	11
Butyl benzl phthalate	20	200
2-chlorophenol	1	7.2
Di-n-butyl phthalate	14	140
Di-n-octyl phthalate	2	20
2,4-Dichlorophenol	1	4
Fluoranthene	5.6	56
Fluorene	5.6	56
Hexachloroethane	1	1
Hexachlorobenzene	1	1
Naphthalene	5.6	56
Pentachlorophenol	1	1
Phenanthrene	4	40
Phenol	80	800
Pyrene	4	40

Regulations of Connecticut State Agencies

Substance	GA, GAA Mobility Criteria in mg/kg (ppm)	GB Mobility Criteria in mg/kg (ppm)
Pesticides and TPH		
Alachlor	0.230	0.4
Aldicarb	1	1
Atrazine	0.2	0.2
Chlordane	0.066	0.066
Dieldrin	0.007	0.007
2-4 D	1.4	14
Heptachlor epoxide	0.02	0.02
Heptachlor	0.013	0.013
Lindane	0.02	0.04
Methoxychlor	0.8	8
Simazine	0.8	8
Toxaphene	0.33	0.6
Total Petroleum Hydrocarbon By EPA Method 418.1 or another EPA-approved method acceptable to the Commissioner (This method shall not be used for the analysis of samples collected after June 30, 2009)	500	2500
Extractable Total Petroleum Hydrocarbons by ETPH Analysis (This method may be used for the analysis of samples collected on or after June 22, 1999)	500	2500
Inorganic Substances and PCB	GA, GAA Mobility Criteria By TCLP or by SPLP in mg/l (ppm)	GB Mobility Criteria By TCLP or by SPLP in mg/l (ppm)

Regulations of Connecticut State Agencies

Antimony	0.006	0.06
Arsenic	0.05	0.5
Barium	1	10.0
Beryllium	0.004	0.04
Cadmium	0.005	0.05
Chromium, total	0.05	0.5
Copper	1.3	13
Cyanide (by SPLP only)	0.2	2
Lead	0.015	0.15
Mercury	0.002	0.02
Nickel	0.1	1.0
Selenium	0.05	0.5
Silver	0.036	0.36
Thallium	0.005	0.05
Vanadium	0.05	0.50
Zinc	5	50
PCB	0.0005	0.005

Appendix C to Sections 22a-133k-1 through 22a-133k-3 of the Regulations of Connecticut State Agencies Direct Exposure Criteria for Soil

Regulations of Connecticut State Agencies

Substance	Ground-water Protection Criteria in ug/l (ppb)
Volatile Organic Substances	
Acetone	700
Acrylonitrile	0.5
Benzene	1
Bromoform	4
2-Butanone(MEK)	400
Carbon tetrachloride	5
Chlorobenzene	100
Chloroform	6
Dibromochloromethane	0.5
1,2-Dichlorobenzene	600
1,3-Dichlorobenzene	600
1,4-Dichlorobenzene	75
1,1-Dichloroethane	70
1,2-Dichloroethane	1
1,1-Dichloroethylene	7
cis-1,2-Dichloroethylene	70
trans-1,2-Dichloroethylene	100
1,2-Dichloropropane	5
1,3-Dichloropropene	0.5
Ethyl benzene	700
Ethylene dibromide (EDB)	0.05
Methyl-tert-butyl-ether	100
Methyl isobutyl ketone	350
Methylene chloride	5
Styrene	100
1,1,1,2-Tetrachloroethane	1
1,1,2,2-Tetrachloroethane	0.5
Tetrachloroethylene	5
Toluene	1000
1,1,1-Trichloroethane	200
1,1,2-Trichloroethane	5
Trichloroethylene	5

Regulations of Connecticut State Agencies

Substance	Ground-water Protection Criteria in ug/l (ppb)
Vinyl chloride	2
Xylenes	530
Semivolatile Substances	
Acenaphthylene	420
Anthracene	2000
Benzo(a)anthracene	0.06
Benzo(b)fluoranthene	0.08
Benzo(k)fluoranthene	0.5
Benzo(a)pyrene	0.2
Bis(2-chloroethyl)ether	12
Bis(2-chloroisopropyl)ether	12
Bis(2-ethyl hexyl)phthalate	2
Butyl benzl phthalate	1000
2-chlorophenol	36
Di-n-butyl phthalate	700
Di-n-octyl phthalate	100
2,4-Dichlorophenol	20
Fluoranthene	280
Fluorene	280
Hexachloroethane	3
Hexachlorobenzene	1
Naphthalene	280
Pentachlorophenol	1
Phenanthrene	200
Phenol	4000
Pyrene	200
Inorganic Substances	
Antimony	6
Arsenic	50
Asbestos in mfl	7 (mfl)
Barium	1000
Beryllium	4
Cadmium	5

Regulations of Connecticut State Agencies

Substance	Ground-water Protection Criteria in ug/l (ppb)
Chromium (total)	50
Copper	1300
Cyanide	200
Lead	15
Mercury	2
Nickel	100
Selenium	50
Silver	36
Thallium	5
Vanadium	50
Zinc	5000
Pesticides, PCB and Total Petroleum Hydrocarbons	
Alachlor	2
Aldicarb	3
Atrazine	3
Chlordane	0.3
Dieldrin	0.002
2-4 D	70
Heptachlor epoxide	0.2
Heptachlor	0.4
Lindane	0.2
Methoxychlor	40
Simazine	4
Toxaphene	3
PCB's	0.5
Total Petroleum Hydrocarbon By EPA Method 418.1 or another EPA-approved method acceptable to the Commissioner (This method shall not be used for the analysis of samples collected after June 30, 2009)	500
Extractable Total Petroleum Hydrocarbons by ETPH Analysis (This method may be used for the analysis of samples collected on or after June 22, 1999)	250

Regulations of Connecticut State Agencies

Appendix D to Sections 22a-133k-1 through 22a-133k-3 of the Regulations of Connecticut State Agencies Direct Exposure Criteria for Soil

Substance	Surface-Water Protection Criteria in ug/l (ppb)
Volatile Organic Substances	
Acrylonitrile	20
Benzene	710
Bromoform	10800
Carbon tetrachloride	132
Chlorobenzene	420000
Chloroform	14100
Dibromochloromethane	1020
1,2-Dichlorobenzene	170000
1,3-Dichlorobenzene	26000
1,4-Dichlorobenzene	26000
1,2-Dichloroethane	2970
1,1-Dichloroethylene	96
1,3-Dichloropropene	34000
Ethylbenzene	580000
Methylene chloride	48000
1,1,2,2-Tetrachloroethane	110
Tetrachloroethylene	88
Toluene	4000000
1,1,1-Trichloroethane	62000
1,1,2-Trichloroethane	1260
Trichloroethylene	2340
Vinyl chloride	15750
Semivolatile Substances	
Acenaphthylene	0.3
Anthracene	1100000
Benzo(a)anthracene	0.3
Benzo(b)fluoranthene	0.3
Benzo(k)fluoranthene	0.3
Benzo(a)pyrene	0.3

Regulations of Connecticut State Agencies

Substance	Surface-Water Protection Criteria in ug/l (ppb)
Bis(2-chloroethyl) ether	42
Bis(2-chloroisopropyl) ether	3400000
Bis(2-ethyl hexyl)phthalate	59
Di-n-butyl phthalate	120000
2,4-Dichlorophenol	15800
Fluoranthene	3700
Fluorene	140000
Hexachloroethane	89
Hexachlorobenzene	0.077
Phenanthrene	0.077
Phenol	92000000
Pyrene	110000
Inorganic Substances	
Antimony	86000
Arsenic	4
Asbestos (in mfl)	7 mfl
Beryllium	4
Cadmium	6
Chromium, trivalent	1200
Chromium, hexavalent	110
Copper	48
Cyanide	52
Lead	13
Mercury	0.4
Nickel	880
Selenium	50
Silver	12
Thallium	63
Zinc	123
Pesticides and PCB	
Chlordane	0.3

Regulations of Connecticut State Agencies

Substance	Surface-Water Protection Criteria in ug/l (ppb)
Dieldrin	0.1
Endrin	0.1
Heptachlor epoxide	0.05
Heptachlor	0.05
Toxaphene	1
PCB's	0.5

Appendix E to Sections 22a-133k-1 through 22a-133k-3 of the Regulations of Connecticut State Agencies Direct Exposure Criteria for Soil

Volatile Substance	Residential Volatilization Criteria for Ground water in parts per billion	Industrial/Commercial Volatilization Criteria for Ground water in parts per billion
Acetone	50000	50000
Benzene	215	530
Bromoform	920	3800
2-Butanone (MEK)	50000	50000
Carbon Tetrachloride	16	40
Chlorobenzene	1800	6150
Chloroform	287	710
1,2-Dichlorobenzene	30500	50000
1,3-Dichlorobenzene	24200	50000
1,4-Dichlorobenzene	50000	50000
1,1-Dichloroethane	34600	50000
1,2-Dichloroethane	21	90
1,1-Dichloroethylene	1	6
1,2-Dichloropropane	14	60
1,3-Dichloropropene	6	25
Ethyl benzene	50000	50000
Ethylene dibromide (EDB)	4	16
Methyl-tert-butyl-ether	50000	50000
Methyl isobutyl ketone	50000	50000
Methylene chloride	50000	50000
Styrene	580	2065

Regulations of Connecticut State Agencies

Volatile Substance	Residential Volatilization Criteria for Ground water in parts per billion	Industrial/Commercial Volatilization Criteria for Ground water in parts per billion
1,1,1,2-Tetrachloroethane	12	50
1,1,2,2-Tetrachloroethane	23	100
Tetrachloroethylene	1500	3820
Toluene	23500	50000
1,1,1-Trichloroethane	20400	50000
1,1,2-Trichloroethane	8000	19600
Trichloroethylene	219	540
Vinyl chloride	2	2
Xylenes	21300	50000

Appendix F to Sections 22a-133k-1 through 22a-133k-3 of the Regulations of Connecticut State Agencies Direct Exposure Criteria for Soil

Volatile Substance	Residential Volatilization Criteria for Soil Vapor in parts per million	Residential Volatilization Criteria for Soil Vapor in milligrams per cubic meter	Industrial/Commercial Volatilization Criteria for Soil Vapor in parts per million	Industrial/Commercial Volatilization Criteria for Soil Vapor in milligrams per cubic meter
Acetone	2400	5701	8250	19597
Benzene	1	3	113	361
Bromoform	1.5	16	6	62
2-Butanone (MEK)	2400	7078	8285	24434
Carbon Tetrachloride	1	6	2.7	17
Chlorobenzene	31	143	106	488
Chloroform	4.5	22	10.4	51
1,2-Dichlorobenzene	240	1443	818	4918
1,3-Dichlorobenzene	240	1443	818	4918
1,4-Dichlorobenzene	950	5712	3270	19661
1,1-Dichloroethane	850	3440	3037	12292
1,2-Dichloroethane	1	4	1	4
1,1-Dichloroethylene	1	4	1	4
1,2-Dichloropropane	1	5	1	5

Regulations of Connecticut State Agencies

Volatile Substance	Residential Volatiliza- tion Criteria for Soil Vapor in parts per million	Residential Volatiliza- tion Criteria for Soil Vapor in milligrams per cubic meter	Industrial/ Commercial Volatiliza- tion Criteria for Soil Vapor in parts per million	Industrial/ Commercial Volatiliza- tion Criteria for Soil Vapor in milligrams per cubic meter
1,3-Dichloropropene	1	5	1	5
Ethyl benzene	1650	7165	5672	24629
Ethylene dibromide (EDB)	1	8	1	8
Methyl-tert-butyl-ether	1000	3605	3415	12312
Methyl isobutyl ketone	140	574	480	1966
Methylene chloride	1200	4168	2907	10098
Styrene	8	34	28	119
1,1,1,2-Tetrachloroethane	1	7	1.5	10
1,1,2,2- Tetrachloroethane	1	7	1	7
Tetrachloroethylene	11	75	27	183
Toluene	760	2864	2615	9855
1,1,1-Trichloroethane	1310	7148	4520	24662
1,1,2-Trichloroethane	40	218	93	507
Trichloroethylene	7	38	16	86
Vinyl chloride	1	3	1	3
Xylenes	500	2192	1702	7461

Appendix G to Sections 22a-133k-1 through 22a-133k-3 of the Regulations of Connecticut State Agencies Direct Exposure Criteria for Soil

Volatilization Criteria for Ground Water

Site-Specific Volatilization Criteria for Ground Water may be calculated using the following equations:

$$GWC = TAC / (1000 \cdot VF_{GW})$$

$$VF_{GW} = \left[\frac{H \left[\left(\frac{D_{EFF-WS}}{L_{GW}} \right) / (ER \cdot L_B) \right] \cdot 1000}{1 + \left[\left(\frac{D_{EFF-WS}}{L_{GW}} \right) / (ER \cdot L_B) \right] + \left[\left(\frac{D_{EFF-WS}}{L_{GW}} \right) / \left(\left(\frac{D_{EFF-CRACK}}{L_{CRACK}} \right) \eta \right) \right]} \right]$$

$$D_{EFF-WS} = (h_{cap} + h_v) /$$

$$D_{EFF-CAP} = D_{AIR} \cdot (\theta_{ACAP}^{3.33} / \theta_T^2) + D_{WATER} / H \cdot (\theta_{WCAP}^{3.33} / \theta_T^2)$$

$$D_{EFF-S} = D_{AIR} \cdot (\theta_{AS}^{3.33} / \theta_T^2) + D_{WATER} / H \cdot (\theta_{WS}^{3.33} / \theta_T^2)$$

$$D_{EFF-CRACK} = D_{AIR} \cdot (\theta_{ACRACK}^{3.33} / \theta_T^2) + D_{WATER} / H \cdot (\theta_{WCRACK}^{3.33} / \theta_T^2)$$

Regulations of Connecticut State Agencies

Where:

Term	Description	Units	Value
GWC	Ground Water Volatilization Criteria	ug/kg	calculated
TAC	Target Indoor Air Concentration	ug/m ³	**
VF _{GW}	Ground Water Volatilization Factor	mg/m ³	calculated
H	Henry's Law Constant	unitless	substance-specific
D _{EFF WS}	Effective Diffusion-Ground Water to Soil Surface	cm ² /s	calculated
L _{GW}	Depth to Ground Water (= h _{CAP} + h _V)	cm	site-specific
h _{CAP}	Thickness of Capillary Fringe	cm	site-specific
h _V	Thickness of Vadose Zone	cm	site-specific
ER _R	Residential Enclosed Space Air Exchange Rate	1/s	.00014
ER _I	Industrial Enclosed Space Air Exchange Rate	1/s	.00023
L _{B R}	Residential Enclosed Space Volume/Infiltration Area Ratio	cm	site-specific
L _{B I}	Industrial Enclosed Space Volume/Infiltration Area Ratio	cm	site-specific
D _{EFF-CRACK}	Effective Diffusion through Foundation Cracks	cm ² /s	calculated
L _{CRACK}	Enclosed Space Foundation or Wall Thickness	cm	site-specific
η	Areal Fraction of Cracks in Foundations / Walls	unitless	.01
D _{EFF-CAP}	Effective Diffusion through Capillary Fringe	cm ² /s	calculated
D _{EFF-S}	Effective Diffusion through Soil (In Vapor Phase)	cm ² /s	calculated
D _{AIR}	Diffusion Coefficient in Air	cm ² /s	8.40E-02 or chemical specific
D _{WATER}	Diffusion Coefficient in Water	cm ² /s	1.00E-05 or chemical specific
θ _{ACAP}	Volumetric Air Content in Capillary Fringe	unitless	site-specific
θ _{AS}	Volumetric Air Content in Vadose Zone	unitless	site-specific
θ _{ACRACK}	Volumetric Air Content in Foundation/Wall Cracks	unitless	site-specific
θ _{WCAP}	Volumetric Water Content in Capillary Fringe	unitless	site-specific

Regulations of Connecticut State Agencies

θ_{WS}	Volumetric Water Content in Vadose Zone	unitless	site-specific
θ_{WCRACK}	Volumetric Water Content in Foundation/Wall Cracks	unitless	site-specific
θ_T	Total Soil Porosity	unitless	site-specific

**See attached “Table of Target Air Concentrations”

Volatilization Criteria for Soil Vapor

Site-Specific Volatilization Criteria for Soil Vapor may be calculated using the following equations:

$$SSVC = TAC / (1000 \cdot VF_{SSV})$$

$$VF_{SSV} = \frac{[(D_{EFF-S} / L_S) / (ER \cdot L_B)]}{1 + [(D_{EFF-S} / L_S) / (ER \cdot L_B)] + [(D_{EFF-S} / L_S) / (D_{EFF-CRACK} / L_{CRACK})] \eta}$$

$$D_{EFF-S} = D_{AIR} \cdot (\theta_{AS}^{3.33} / \theta_T^2) + D_{WATER} / H \cdot (\theta_{WS}^{3.33} / \theta_T^2)$$

$$D_{EFF-CRACK} = D_{AIR} \cdot (\theta_{ACRACK}^{3.33} / \theta_T^2) + D_{WATER} / H \cdot (\theta_{WCRACK}^{3.33} / \theta_T^2)$$

Where:

Terms	Description	Units	Value
SSVC	Volatilization Criteria for Soil Vapor	mg/m ³ -air	calculated
TAC	Target Indoor Air Concentration	ug/m ³ -air	**
VF _{SSV}	Volatilization Factor for Subsurface Vapors	unitless	calculated
H	Henry’s Law Constant	unitless	substance-specific
D _{EFF-S}	Effective Diffusion through Soil (in Vapor Phase)	cm ² /s	calculated
L _S	Depth to Soil Vapor Sample	cm	site-specific
ER _R	Residential Enclosed Space Air Exchange Rate	1/s	.00014
ER _I	Industrial Enclosed Space Air Exchange Rate	1/s	.00023
L _{B-R}	Residential Enclosed Space Volume/Infiltration Area Ratio	cm	site-specific
L _{B-I}	Industrial Enclosed Space Volume/Infiltration Area Ratio	cm	site-specific
D _{EFF-CRACK}	Effective Diffusion through Foundation Cracks	cm ² /s	calculated
L _{CRACK}	Enclosed Space Foundation or Wall Thickness	cm	site-specific

Regulations of Connecticut State Agencies

Terms	Description	Units	Value
η	Areal Fraction of Cracks in Foundations / Walls	unitless	calculated
θ_{AS}	Volumetric Air Content in Vadose Zone	unitless	site-specific
θ_{ACRACK}	Volumetric Air Content in Foundation/Wall Cracks	unitless	site-specific
θ_{WS}	Volumetric Water Content in Vadose Zone	unitless	site-specific
θ_{WCRACK}	Volumetric Water Content in Foundation/Wall Cracks	unitless	site-specific
θ_T	Total Soil Porosity	unitless	site-specific

** See attached "Table of Target Air Concentrations"

Table of Target Air Concentrations

Volatile Substance	Residential Target Indoor Air Concentration in micrograms per cubic meter	Industrial/Commercial Target Indoor Air Concentration in micrograms per cubic meter
Acetone	8.34 E02	1.17 E03
Benzene	3.25 E00	2.15 E01
Bromoform	2.21 E00	3.72 E00
2-Butanone (MEK)	1.04 E03	1.46 E03
Carbon Tetrachloride	1.00 E00	1.00 E00
Chlorobenzene	2.09 E01	2.92 E01
Chloroform	3.00 E00	3.00 E00
1,2-Dichlorobenzene	2.09 E02	2.92 E02
1,3-Dichlorobenzene	2.09 E02	2.92 E02
1,4-Dichlorobenzene	8.34 E02	1.17 E03
1,1-Dichloroethane	5.21 E02	7.30 E02
1,2-Dichloroethane	9.36 E-02	1.57 E-01
1,1-Dichloroethylene	4.87 E-02	8.18 E-02
1,2-Dichloropropane	1.28 E-01	2.15 E-01
1,3-Dichloropropene	6.58 E-02	1.10 E-01
Ethyl benzene	1.04 E03	1.46 E03
Ethylene dibromide (EDB)	1.11 E-02	1.86 E-02
Methyl-tert-butyl-ether	5.21 E02	7.30 E02
Methyl isobutyl ketone	8.34 E01	1.17 E02
Methylene chloride	6.00 E02	6.00 E02

Regulations of Connecticut State Agencies

Volatile Substance	Residential Target Indoor Air Concentration in micrograms per cubic meter	Industrial/Commercial Target Indoor Air Concentration in micrograms per cubic meter
Styrene	5.00 E00	7.17 E00
1,1,1,2-Tetrachloroethane	3.29 E-01	5.52 E-01
1,1,2,2-Tetrachloroethane	4.20 E-02	7.05 E-02
Tetrachloroethylene	1.10 E01	1.10 E01
Toluene	4.17 E02	5.84 E02
1,1,1-Trichloroethane	1.04 E03	1.46 E03
1,1,2-Trichloroethane	3.00 E01	3.00 E01
Trichloroethylene	5.00 E00	5.00 E00
Vinyl chloride	2.90 E-02	4.87 E-02
Xylenes	3.13 E02	4.38 E02

(Effective January 30, 1996; Amended June 27, 2013)